# Specification: SnapWay<sup>TM</sup> 2400 SERIES

## PART 1 - GENERAL

## 1.10 DESCRIPTION

- A MONO-SYSTEMS, INC. two compartment SnapWay<sup>TM</sup> series SWA2400. The two components being:
  - 1. BASE SECTION SnapWay<sup>TM</sup> main unit.
  - 2. The base sections shall be nominally 10' long (3m) and x 2" X .73" (50mm X 19mm).

#### 1.20 SUBMITTALS

- A. SHOP DRAWINGS
  - 1. Catalog cuts
    - a. Device plates
    - b. Material sections
    - c. Accessories
    - d. Internal area descriptions

#### **PART 2 - PRODUCTS**

## 2.10 MATERIALS

- A. Surface metal raceway to be provided as shown on drawings.
- B. The base and cover sections shall be manufactured of 6063-T6 aluminum alloy with a nominal material thickness of .053" (1.35mm). The surface finish shall be satin anodized #204 type clear, Class R1 MIL-SPEC with a minimum finish of .004".

#### 2.11 COVERS

- A. Cover sections shall be nominally 5' long (1.5m)
- B. Standard duplex receptacle openings 20A/125V (NEMA 5-15R) to be provided by others as specified. Standard dimension for center of receptacle openings shall be 6 inches (152mm).

#### 2.12 INSTALLATION

- A. The electrical contractor shall furnish and install all surface metal raceways complete with appropriate fittings. All fittings shall be furnished by the raceway manufacturer.
- B. The electrical contractor shall provide grounding per the National Electric Code and Local Codes.
- C. All surface metal raceways shall be installed parallel with, and perpendicular to the structure. All exposed edges, where field cut, shall be coated by the electrical contractor to prevent corrosion.
- D. Field cut straight cover sections between specific device covers.
- E. All raceways shall be electrically continuous, in compliance with applicable UL standards. All raceway and fittings shall meet the requirements of NEC article 352A.

## 2.13 SUPPLY THE FOLLOWING MATERIAL FOR THIS PROJECT:

- A. BASE SECTIONS SWA2400
- B. COVER SECTIONS SWA2403
- C. SPLICE CONNECTORS SWA2402
- D. MANUFACTURED FITTINGS (Consult MonosSystems Inc directly as to components required to complete installation)

# PART 3 - MANUFACTURER

- A. SnapWay<sup>TM</sup> shall be manufactured by MONO-SYSTEMS, INC.,
- 4 INTERNATIONAL DRIVE, RYE BROOK, NY 10573
- (TEL) 914-934-2075 (FAX) 914-934-2190.